



CKTS	DIM. "A"	DIM. "B"
2	1.25	7.7
3	2.50	8.9
4	3.75	10.2
5	5.00	11.4
6	6.25	12.7
7	7.50	13.9
8	8.75	15.2
9	10.00	16.4
10	11.25	17.7
11	12.50	18.8
12	13.75	20.2
13	15.00	21.4
14	16.25	22.7
15	17.50	23.9

NOTES

- * Poles:2~15
 - * Insulator:high temperature plastic UL94V-0
HTN6T UL94V-0
 - * Contact:phosphor bronze Matte Tin-plated
 - * Mates with CH1251-XX series housing
- Specifications**
- * Current rating: 1A AC, DC
 - * Voltage rating: 125V AC, DC
 - * Temperature range: -40°C~+85°C
 - * Insulation resistance: 100M Ω min.
 - * Withstand voltage: 250 AC/minute

ORDERING CODE

HW1252 ST - XX M - C - R
① ② ③ ④ ⑤ ⑥

- ① SERIES NO.
- ② TERMINAT TYPE
ST=180° SMT
- ③ NO. OF CIRCUIT
- ④ CONTACT PLATED
M=MATTE TIN PLATED
- ⑤ CAP OPTION
C=W/CAP
N=W/O CAP
- ⑥ PACKING OPTION
T: TUBE
R: TAPE REEL

詮盛企業股份有限公司 CHIEN SHERN ENTERPRISE CO.,LTD.	TITLE	1.25mm pitch sraight angle SMT type	TOLERANCE	DRAWN		DATE	2015.10.25
	PART NO.	HW1252ST-XXM-C-R	DIM.	CHECK		DATE	
	DWG.NO.	HW1252ST-XXM-C-R	0.0 ±0.30	APPROVE		DATE	
			0.00 ±0.20	SCALE		UNIT	mm