



P.C. Board Layout



MATERIAL :

- * Insulator: HTN6T UL94V-0 Natural
 - * Pin: Brass Matte Tin-Plated
 - * Mates with CH1251-XX series housing
- #### SPECIFICATIONS
- * Current rating: 1A AC, DC
 - * Voltage rating: 125V AC, DC
 - * Temperature range: -25°C~+85°C
 - * Insulation resistance: 100MΩ min.
 - * Dielectric Withstand voltage: 250V AC/minute

Matte

CKTS	PART NO.	DIM. "A"	DIM. "B"
2	HW1252RP-02T	1.25	4.25
3	HW1252RP-03T	2.50	5.50
4	HW1252RP-04T	3.75	6.75
5	HW1252RP-05T	5.00	8.00
6	HW1252RP-06T	6.25	9.25
7	HW1252RP-07T	7.50	10.50
8	HW1252RP-08T	8.75	11.75
9	HW1252RP-09T	10.00	13.00
10	HW1252RP-10T	11.25	14.25
11	HW1252RP-11T	12.50	15.50
12	HW1252RP-12T	13.75	16.75
13	HW1252RP-13T	15.00	18.00
14	HW1252RP-14T	16.25	19.25
15	HW1252RP-15T	17.50	20.50

詮盛企業股份有限公司 CHIEN SHERN ENTERPRISE CO.,LTD.	TITLE	1.25mm pitch single row Headers DIP TYPE	TOLERANCE	DRAWN		DATE	2022.08.10
	PART NO.	HW1252RP-XXT	DIM. 0.0 ±0.25	CHECK		DATE	
	DWG.NO.	HW1252RP-XXT	0.00 ±0.20	APPROVE		DATE	
			0.000 ±0.08	SCALE		UNIT	mm