



P.C. Board Layout



MATERIAL :

- * Insulator: HTN6T UL94V-0 Natural
 - * Pin: Brass Matte Tin-Plated
 - * Mates with CH1251-XX series housing
- # SPECIFICATIONS
- * Current rating: 1A AC, DC
 - * Voltage rating: 125V AC, DC
 - * Temperature range: $-25^{\circ}\text{C} \sim +85^{\circ}\text{C}$
 - * Insulation resistance: $100\text{M}\Omega$ min.
 - * Dielectric Withstand voltage: 250V AC/minute

CKTS	PART NO.	DIM. "A"	DIM. "B"
2	HW1252SP-02T	1.25	4.25
3	HW1252SP-03T	2.50	5.50
4	HW1252SP-04T	3.75	6.75
5	HW1252SP-05T	5.00	8.00
6	HW1252SP-06T	6.25	9.25
7	HW1252SP-07T	7.50	10.50
8	HW1252SP-08T	8.75	11.75
9	HW1252SP-09T	10.00	13.00
10	HW1252SP-10T	11.25	14.25
11	HW1252SP-11T	12.50	15.50
12	HW1252SP-12T	13.75	16.75
13	HW1252SP-13T	15.00	18.00
14	HW1252SP-14T	16.25	19.25
15	HW1252SP-15T	17.50	20.50

詮盛企業股份有限公司

CHIEN SHERN ENTERPRISE CO.,LTD.

TITLE

1.25mm pitch single row Headers DIP TYPE

PART NO.

HW1252SP-XXT

DWG.NO.

HW1252SP-XXT

TOLERANCE

DIM.

0.0 ± 0.25

0.00 ± 0.20

0.000 ± 0.08

DRAWN

CHECK

APPROVE

SCALE

DATE

DATE

DATE

UNIT

2022.08.10

mm