










P/N: CH4257-03



P/N: CH4257S-03



P/N: CH4257-XX SERIES



CH4257 Series

- * Poles: 2-12
- * Material: NYLON 66 UL94V-2 natural
- * Suitable CT4201T series terminal
- * Mates with CH4259-XX series Housing or CW4266S, CW4269R-XX Series Header

SPECIFICATIONS

- * Current rating: 8A AC DC
- * Voltage rating: 500V AC DC
- * Temperature range: -25°C~+85°C
- * Insulation resistance: 1,000MΩ min.
- * Withstand voltage: 1,500AC/minute

TOLERANCE:

- 2~6P: A±0.20 B±0.30
- 7~12P: A±0.30 B±0.40

CKTS	Dim.A	Dim.B	CKTS	Dim.A	Dim.B
2	4.2	9.8	8	29.4	34.8
3	8.4	14.0	9	33.6	39.0
4	12.6	18.2	10	37.8	43.2
5	16.8	22.4	11	42.0	47.4
6	21.0	26.6	12	46.2	51.6
7	25.2	30.6			

詮盛企業股份有限公司

CHIEN SHERN ENTERPRISE CO.,LTD.

TITLE	4.20mm Pitch Single Row (Receptacle)	GENERAL TOLERANCE	DRAWN	許建華	DATE	2008.01.21
PART NO.	CH4257-XX	DIM. .0 ±0.30	CHECK		DATE	
DWG.NO.	CH4257-XX	.00 ±0.20	APPROVE		DATE	
		.000 ±0.10	SCALE		UNIT	mm
					REV.	01