

.050"(1.27mm) Pitch FFC/FPC Housing Connectors




P/N: HF1270A-XX Series



- * Material: PBT UL94V-0 Black
- * Suitable TF1270T series terminal
- * Mates with P1271X-XX series pin Header

Specifications

- * Current rating: 1A AC, DC
- * Voltage rating: 100V AC, DC
- * Temperature range: -25°C~+85°C



inches
mm



CKTS	PART NO.	DIM. "A"	DIM. "B"	CKTS	PART NO.	DIM. "A"	DIM. "B"
4	HF1270A-04	0.150(3.81)	0.242(6.15)	15	HF1270A-15	0.700(17.78)	0.792(20.12)
5	HF1270A-05	0.200(5.08)	0.292(7.42)	16	HF1270A-16	0.750(19.05)	0.842(21.39)
6	HF1270A-06	0.250(6.35)	0.342(8.69)	17	HF1270A-17	0.800(20.32)	0.892(22.66)
7	HF1270A-07	0.300(7.62)	0.392(9.96)	20	HF1270A-20	0.950(24.13)	1.042(26.47)
8	HF1270A-08	0.350(8.89)	0.442(11.23)	22	HF1270A-22	1.050(26.67)	1.142(29.01)
10	HF1270A-10	0.450(11.43)	0.542(13.77)	25	HF1270A-25	1.200(30.48)	1.292(32.82)
11	HF1270A-11	0.500(12.70)	0.592(15.04)	26	HF1270A-26	1.250(31.75)	1.342(34.09)
12	HF1270A-12	0.550(13.97)	0.642(16.31)	30	HF1270A-30	1.450(36.83)	1.542(39.17)
13	HF1270A-13	0.600(15.24)	0.692(17.58)				

.050"(1.27mm) Pitch FFC/FPC crimp terminal

P/N: TF1270T

Crimp Female Terminal

Mates 0.40mm square pin.

Material: Phosphor Bronze

Finished: Tin Plated

Used in HF1270A-XX, HF1270B-XX

HF1272X-2xXX series housing

Q'TY: 30,000pcs/reel

inches
mm

P/N: TF1270B6T

Crimp Male Terminal

Suitable for flexible Solder Tab

Material: phosphor bronze

Finished: Tin Plated

Q'TY: 30,000pcs/reel

