



P.C. Board Layout

CIRCUITS	DIM. A	DIM. B
2	1.25	7.7
3	2.50	8.9
4	3.75	10.2
5	5.00	11.4
6	6.25	12.7
7	7.50	13.9
8	8.75	15.2
9	10.00	16.4
10	11.25	17.7
11	12.50	18.6
12	13.75	20.2
13	15.00	21.4
14	16.25	22.7
15	17.50	23.9

NOTES

- * Poles:2~15
 - * Insulator:high temperature plastic
HTN6T UL94V-0
 - * Contact:phosphor bronze Matte Tin-plated
 - * Tab:Brass Matte Tin plated
 - * Mates with CH1251-XX series housing
- Specifications
- * Current rating: 1A AC, DC
 - * Voltage rating: 125V AC, DC
 - * Temperature range: -40°C~+85°C
 - * Insulation resistance: 100MΩ min.
 - * Withstand voltage: 250 AC/minute

ORDERING CODE

HW1252 RT - XX M - R
 ① ② ③ ④ ⑤

- ① SERIES NO.
- ② TERMINAL TYPE
RT=RIGHT ANGLE SMT
- ③ NO. OF CIRCUIT
- ④ CONTACT PLATED
M=MATTE TIN PLATED
- ⑤ PACKING OPTION
T=TUBE
R=TAPE REEL

詮盛企業股份有限公司 CHIEN SHERN ENTERPRISE CO.,LTD.	TITLE	1.25mm pitch Right Angle SMT TYPE	GENERAL TOLERANCE	DRAWN	DATE	2015.10.25		
	PART NO.	HW1252RT-XXM-R	DIM: X. ±0.5 X.X ±0.25 X.XX ±0.2 X.XXX ±0.08	CHECK	DATE			
	DWG.NO.	HW1252RT-XXM-R		APPROVE	DATE			
				SCALE	UNIT	mm	REV.	01