



RECOMMEND P.C.B. LAYOUT
TOP VIEW

***Specification:**

- 1.Housing: Thermoplastic UL 94V-0, Color: Black;
- 2.Contact: Phosphor Bronze;
- 3.Contact Plating: Gold Plating Over Nickel on Contact Area, Tin/Lead Plating on Solder Tail
- 4.Current Rating: 0.5 AMP. Max.;
- 5.Dielectric Withstanding Voltage: 500V AC R.M.S For One Minute;
- 6.Insulation Resistance: 1000 M Ohms Min. AT DC 500V
- 7.Contact Resistance: 50 M Ohms Max.;
- 8.Operating Temperature: -25°C to +85°C;
- 9.Processing Temp: 260°C for 15 Seconds Max.;

ORDER INFORMATION

SIM40-08 SA 0 R
1 2 3 4 5

1. SERIES NO
2. NO. OF POS
3. CONTACT PLATED
SA=SELECTIVE GOLD FLASH
4. POST OPTION
0=W/O LOCATING PEG
1=W/LOCATING PEG
5. PACKING
R=TAPE&REEL

詮盛企業股份有限公司

CHIEN SHERN ENTERPRISE CO.,LTD.

TITLE SIM CARD CONN WITH COVER

PART NO. SIM40-08SA0R

DWG.NO. SIM40-08SA0R

GENERAL TOLERANCE

DIM:
X. ±0.5
X.X ±0.25
X.XX ±0.2
X.XXX ±0.08

DRAWN

CHECK

APPROVE

SCALE

許建華

DATE

DATE

UNIT

DATE

DATE

UNIT

mm

2005.11.02

DATE

DATE

REV. 01